



Technical information

WipeEx SA120[®]

ReadyMix



Technical Data

Density at 20°C	0,96 g/cm ³
Viscosity at 20°C	1,0 mPas
ph-value at 20°C	7,0 at 10g/l
Boiling temperature	none
Explosion risk	none
Solubility in water	unlimited
Application temperature	20 - 45° C
Application	pure
Storing	0 - 40°C
Waste key	07 01 04
WPC	2
Hazards classification	no marking required

Water based pH-neutral cleaning Ready-Mix for the machine cleaning with fleece of underscreen cleaning in screen printers

Cleans SMD-adhesive and SMD-paste

ReadyMix for direct application in a cleaning tank of screen printers

Applications

Cleaning of:	
SMD adhesive	++*
SMD solder paste	++*

Please be aware: The product may irritate mucuous membrane, skin and eyes!

For commercial use only!

Your WipeEx SA120 supplier:

Process

	Manual cleaning
	Stencil under-/flipside

Part No. 090616-2 // PU: 2 x 5 l

Part No.

Made in Germany

Part No.

***++ = ideal for application, + = recommended, o = usable but not recommended, - = not recommended**

Note: The spreadsheet only shows a general overview of the cleaning media specifications. Rinsing with tap water with a too high lime concentration may cause lime residues after drying. Cleaning tests are reasonable and necessary to determine the optimum cleaner configuration. Such tests may be carried out directly at the **kolb** Demonstration Center in Willich / Germany or can be initiated by contacting one of our international subsidiaries.

Kolb Cleaning Technology GmbH
 Karl-Arnold-Str. 12 · D - 47877 Willich
 Further information: www.kolb-ct.com

Phone +49 (0) 2154 9479 - 38
 Fax +49 (0) 2154 9479 - 47
 e-mail info@kolb-ct.com

All modifications due to technical improvements are subject to change without notice.